

Macron® 2438 M-8 US

Neat cutting oil

DESCRIPTION

Macron 2438 M-8 US is used for gear grinding and honing applications, with ceramic, diamond and boron nitride (CBN) grinding wheels on Reishauer, Kapp, Junker or Klingenberg machines. The product is also suitable for general machining of alloyed steels, yellow metal and aluminium alloys.

Macron 2438 M-8 US is based on synthetic oil with a very low aromatic content, which guarantees low evaporation. The product is free of chlorine and of heavy metals. A combination of polar, extreme pressure and anti-wear additives provides the oil with high load carrying properties.

FEATURES / BENEFITS

- Long tool life
- Excellent surface finish of the machined work pieces

With **Macron 2438 M-8 US**, there is no risk of staining yellow metals.

DATA (TYPICAL VALUES)

Appearance	Light Yellow
Pounds per Gallon	7.05
Kinematic Viscosity @ 40°C: cSt	8.0
Flashpoint COC °C	> 170

HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

DM 15.04 US



Houghton International Inc.
 Madison and Van Buren Aves.
 P. O. Box 930
 Valley Forge, PA 19482-0930

Phone: 610-666-4000
 Fax: 610-666-0174
 info@houghtonintl.com
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.