

Rust Veto® 2212-B

Biostable, synthetic aqueous base rust preventative

DESCRIPTION

Rust Veto 2212-B is a biostable all synthetic aqueous base rust preventive, which has the features of a non-nitrited chemical rust inhibitor. It is recommended for use at 3-5% concentration. It forms a clear solution and is recommended for use on ferrous and nonferrous metals.

Rust Veto 2212-B is an excellent choice in processes following cleaning, and in heat treatment where short-term indoor protection is desired. Being totally synthetic, the residual film can be easily removed in subsequent operations, and does not contribute to tramp oil concerns.

Rust Veto 2212-B can also be used as a hydro-static test solution.

FEATURES / BENEFITS

- No oil - eliminates disposal problems common with water base preservation
- No nitrites - eliminates health hazard associated with this chemical
- Hard water stable - solutions are stable in hard water up to 500ppm while retaining rust protection
- Thin film protects your parts without excessive carry-off which reduces usage and cost.
- Low-odor nature of the product optimizes worker acceptance.
- Rapid drying permits handling of parts shortly after application which expedites process flow and packaging.

DATA (TYPICAL VALUES)

Appearance	Clear, amber fluid
Total Alkalinity	9.7 % as KOH
pH, (neat)	9.73
pH, (5% Solution)	9.4
Lbs./gal.	8.49
Free Caustic	None
Solubility	Freely soluble
Operating Temperatures	Ambient to 140°F
Use Concentration	3 - 5% by volume
Cast Iron Chip Test	Passes @ 3%

HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

EN 15.02 US



Houghton International Inc.
 Madison and Van Buren Aves.
 P. O. Box 930
 Valley Forge, PA 19482-0930

Phone: 610-666-4000
 Fax: 610-666-0174
 info@houghtonintl.com
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.