

Cerfa-Kleen® 5285-US

A non-silicated spray wash cleaner

DESCRIPTION

Cerfa-Kleen 5285-US is an alkaline liquid spray washer cleaner with automotive OEM approvals.

Cerfa-Kleen 5285-US is free rinsing and will not leave a residue which could affect finishing operations, such as plating. It is safe for both ferrous and non-ferrous materials.

INSTRUCTIONS FOR USE

Cerfa-Kleen 5285-US is designed to be used as spray washer at concentrations of 2 to 5% by volume, depending on the soil being removed and metal being processed. The operating temperature ranges from ambient to 140°F.

DATA (TYPICAL VALUES)

Appearance	Clear, pale straw liquid
Solubility	Miscible with water in all proportions
Operating pH (2% Solution)	8.8 to 9.2
Silicates	None
Operating Temperature	Ambient to 140°F

FEATURES / BENEFITS

- Outstanding cleaning capability for optimal soil removal.
- May be used at ambient temperatures to dramatically reduce energy costs.
- Biostable technology extends sump life and reduces need for costly sumpside biocide addition.
- Imparts corrosion inhibition to parts to protect them from rusting between operations thereby reducing scrap rates.
- Incorporates corrosion inhibitors that prevent flash rusting of your machinery.
- Works on a wide variety of alloys which reduces costs via consolidation of products and purchases.

HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

EN 15.02 US



Houghton International Inc.
 Madison and Van Buren Aves.
 P. O. Box 930
 Valley Forge, PA 19482-0930

Phone: 610-666-4000
 Fax: 610-666-0174
 info@houghtonintl.com
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.