

# Dasco<sup>®</sup> Arc 206-HF

## High flash point solvent type rust preventative

### DESCRIPTION

Dasco ARC 206-HF is a high quality solvent based rust preventative with water displacing properties and a high flash point.

Dasco ARC 206-HF provides medium term indoor rust protection.

Dasco ARC 206-HF leaves an oily film which can be removed with a solvent or hot alkali wash.

Dasco ARC 206-HF is used undiluted and can be applied by brush, dip or spray.

### FEATURES / BENEFITS

- Provides excellent medium term indoor rust protection
- Excellent water displacing properties
- High flash point
- Used as supplied, no dilution required
- Applied by brush, spray or dip
- Easily removed with solvents or hot alkaline cleaners
- Oily film

### Rust Protection Tests

Tests on cold rolled, mild steel panels

In Plant Protection:

110 days with no rust (Spring to Fall)

Humidity Cabinet ASTM D-1748

8 days no rust (40°C, 95-100% RH)

### DATA (TYPICAL VALUES)

Appearance	Clear amber fluid
Specific Gravity @ 15°C	0.872
Viscosity @ 40°C	3.1 cSt
Flash Point °C	98.9
Film Type	Oily

### HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

EN 14.04 US



Houghton International Inc.  
 Madison and Van Buren Aves.  
 P. O. Box 930  
 Valley Forge, PA 19482-0930

Phone: 610-666-4000  
 Fax: 610-666-0174  
 info@houghtonintl.com  
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.