

# Rust Veto® 210

Light oil rust preventive

## DESCRIPTION

Houghton's **Rust Veto 210** is an oil rust preventive that displaces and separates water on flat or round wire stock and tube stock. It can be applied by brush, spray, or dip methods and leaves a light oil film on parts or equipment. Excess material drains rapidly from treated surfaces because of the preventive's light viscosity

## FEATURES / BENEFITS

- Excellent humidity rust protection
- Easily removed
- Barium free
- Low-odor nature of the products optimizes worker acceptance.
- Displaces water or process fluids from wet parts to rapidly begin the corrosion inhibition process.
- Separates any displaced water from itself to optimize both corrosion inhibition and bath life.
- The high flash point reduces the potential for flammability and may reduce fire insurance premiums.

## DATA (TYPICAL VALUES)

Flash Point, °F	360
Fire Point, °F	365
Kinematic Viscosity @ 100°F (38°C)	24 cSt
Pour Point, °F	-14 (-25°C)
Approx. Coverage, sq. ft./gal.	3000
Film Thickness	.45 MIL
Humidity Test @ 120°F (polished panels) (ASTM D-1748)	Pass 30+ days
5% Salt Spray @ 95°F	4-5 hours

## HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

EN 14.12 US



Houghton International Inc.  
 Madison and Van Buren Aves.  
 P. O. Box 930  
 Valley Forge, PA 19482-0930

Phone: 610-666-4000  
 Fax: 610-666-0174  
 info@houghtonintl.com  
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.