

Rust Veto® 2147

Rust preventative

DESCRIPTION

Rust Veto 2147 was specifically developed to provide long-term rust inhibition of cast iron, but is also an ideal product for regular steel as well.

One gallon covers 1,900 square feet. The polar attraction for metal makes **Rust Veto 2147** "creep" across the metal's surface, spreading over a large area. This affinity for metal means handling won't wipe it off.

Rust Veto 2147 contains an antioxidant additive. It resists breakdown and varnish formation, even in long-term storage. Apply by dip or spray.

DATA (TYPICAL VALUES)

| | |
|---------------------------|-----------------------------|
| Appearance | Dark amber fluid |
| Film Thickness | 0.00046" |
| Film Character | Thin, oily, and transparent |
| Viscosity @ 100°F | 60 SUS |
| Flash Point, PMCC | 190°F |
| Pounds per Gallon | 7.26 |
| Specific Gravity 60°/60°F | .872 |
| Coverage | 1,900 sq. ft./gal |
| V.O.C. | 3.16 lbs./gallon |

FEATURES / BENEFITS

- Thin film protects your parts without excessive carry-off which reduces usage and cost.
- Low-odor nature of the products optimizes worker acceptance.
- The high flash point reduces the potential for flammability and may reduce fire insurance premiums.
- Rapid drying permits handling of parts shortly after application which expedites process flow and packaging.

PROTECTIVE PROPERTIES

| | |
|--|------------|
| Salt Spray, ASTM B117 (95°F/100% R.H.) | 3 days |
| Humidity Cabinet* | 30+ days |
| Humidity Cabinet** | 25 days |
| Indoor Protection - unwrapped | 12+ months |
| Shed Protection | 4-6 months |

* Polished, mild steel panels dipped into the neat product; allowed to dry overnight; cabinet conditions: 120°F and 100% relative humidity.

** Cast Iron Panels tested @ 100°F/100% RH

HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

HL 12.08 US



Houghton International Inc.
 Madison and Van Buren Aves.
 P. O. Box 930
 Valley Forge, PA 19482-0930

Phone: 610-666-4000
 Fax: 610-666-0174
 info@houghtonintl.com
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.