

Rust Veto[®] 2186

Rust preventative

DESCRIPTION

Rust Veto 2186 is especially designed to provide long-term protection of steel parts. It can be used on ferrous fabrications exposed to high temperature and high humidity conditions. The product leaves a thin oily film when dried and exhibits very good water separating and water displacement characteristics. It is highly compatible with alkaline cleaners and synthetic coolants, commonly used in high production applications.

DATA (TYPICAL VALUES)

Appearance	Clear, amber fluid
Specific Gravity @ 60°F (15.6°C)	.852
Pounds per Gallon	7.1
Non-Volatile, %	55.0
Flash Point (PMCC)	180°F
30 Day Humidity Test 120 °F @ 100% RH	Passes
Film Type	Thin, oily - 0.42 mls
Cloud Point	+8°F (-15°C)
Pour Point	-26°F
Freeze Point	-31°F
H2O Separation	Passes
H2O Displacement	Passes
Alkaline Resistance	Passes
Coverage	1900 sq. ft. per gallon

FEATURES / BENEFITS

- Thin oily film
- Easy to apply - dip, brush or spray
- Excellent protection
- High flash - 180°F, PMCC
- Displaces water
- Fast water separation
- Easily removed
- For use with all metals
- Barium-free
- Alkaline resistance
- Low freeze and pour point
- Good wetting properties

HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

HL 13.12 US



Houghton International Inc.
 Madison and Van Buren Aves.
 P. O. Box 930
 Valley Forge, PA 19482-0930

Phone: 610-666-4000
 Fax: 610-666-0174
 info@houghtonintl.com
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.