

Rust Veto[®] 4214

Rust preventative

DESCRIPTION

Rust Veto 4214 is a rust preventative that is exceptionally stable in wet conditions, particularly where there is alkaline, acid or solvent emulsion rinse water left on parts. It offers prolonged effectiveness where rinsing is not always thorough. **Rust Veto 4214** releases displaced water within minutes and, on evaporation, leaves a very thin, transparent protective film. It provides indoor protection for as long as 12 months, particularly if parts are packaged.

FEATURES / BENEFITS

- Easy to apply - displaces and separates water fast
- Exceptional stability - even in acid or alkaline conditions
- Flash Point - 105°F minimum (PMCC)
- Excellent humidity protection
- Easily removed

DATA (TYPICAL VALUES)

Type of Film	Thin oily, transparent
Flash Point, typical, PMCC	105°F
Viscosity @ 100°F, SUS	32
Film Thickness	.1 mil
Coverage	1900 ft.2/gal.
Application Method	Dip, spray or brush
Dry to Set Time	1 - 2 hours
Type of Protection	High humidity and fingerprint suppression
% Non-Volatile	12%
Metal Compatibility	All metals

HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

HL 13.12 US



Houghton International Inc.
 Madison and Van Buren Aves.
 P. O. Box 930
 Valley Forge, PA 19482-0930

Phone: 610-666-4000
 Fax: 610-666-0174
 info@houghtonintl.com
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.